

The right choice of your spray gun !

# Application Recommendation

Wall Painting/Window Construction



Finding the right SATA spray gun for your material

| SATA LM 2000 B RP | SATA LM 2000 HVLP | SATA Spray Master | SATAjet B/GR | SATAjet RP   | SATAjet 2000 HVLP | SATA Spray-Mix 1:32 |  |
|-------------------|-------------------|-------------------|--------------|--------------|-------------------|---------------------|--|
| 2,0               | 2,1               | SM<br>0,3-0,8**   | 2,0          | 2,0          | 2,2               | 2350<br>2850        | Rubbol Primer<br>Rubbol Undercoat                      |
| 2-3 bar           | 3 bar             | 1,5-3<br>bar*     | 3-4 bar      | 1,5-2<br>bar | 2 bar             | 3/3 bar*            |  |
| 2,0<br>2,5        |                   | SM<br>0,3-0,8**   | 2,0-<br>2,5  | 2,0-<br>2,5  | 2,2               | 2850                | Rubbol Inside Filler L<br>Rubbol Inside Filler S       |
| 2-3 bar           |                   | 1,5-3<br>bar*     | 2-3 bar      | 1,5-2<br>bar | 2 bar             | 3/3 bar*            |  |
| 1,6-<br>2,0       | 1,9               | SM<br>0,3-0,8**   | 1,7-<br>2,0  | 1,6-<br>2,0  | 1,7-<br>2,2       | 2350<br>2850        | Rubbol Azura<br>Rubbol Satura                          |
| 2-3 bar           | 3 bar             | 1,5-3<br>bar*     | 3-4 bar      | 1,5-2<br>bar | 2 bar             | 3/3 bar*            |  |
| 1,6-<br>1,8       | 1,7-1,9           |                   | 1,7-<br>2,0  | 1,6-<br>2,0  | 1,7-<br>1,9       | 2350<br>2850        | Rubbol BL Isoprimer                                    |
| 2-3 bar           | 3 bar             |                   | 3-4 bar      | 1,5-2<br>bar | 2 bar             | 3/3*                |  |
| 1,6-<br>1,8       | 1,7-1,9           |                   | 1,7-<br>2,0  | 1,6-<br>2,0  | 1,7-<br>1,9       | 2350<br>2850        | Rubbol BL Azura<br>Rubbol BL Satura<br>Rubbol BL Satin |
| 2-3 bar           | 3 bar             |                   | 3-4 bar      | 1,5-2<br>bar | 2 bar             | 3/3*                |  |
| 1,6-<br>1,8       | 1,7-1,9           |                   | 1,7-<br>2,0  | 1,6-<br>2,0  | 1,7-<br>1,9       | 2350<br>2850        | Cetol BL Unitop  |
| 2-3 bar           | 3 bar             |                   | 3-4 bar      | 1,5-2<br>bar | 2 bar             | 3/3 bar*            |  |
|                   |                   | SM<br>0,2-0,5**   |              |              |                   | 2850<br>3350        | Cetol WF 750/755<br>Cetol WF 770                       |
|                   |                   | 2-3 bar*          |              |              |                   | 3/3*                |  |
|                   |                   | SM<br>0,3-0,8**   |              |              |                   | 2850<br>3350        | Rubbol WF 368/370                                      |
|                   |                   | 2-3 bar*          |              |              |                   | 3/3*                |  |
|                   |                   |                   |              |              |                   |                     |  |
|                   |                   |                   |              |              |                   |                     |  |

Please read the technical details of the recommended spray gun types in our operating manual on our website [www.sata.de](http://www.sata.de). E.&O.E. Technical alterations reserved. 4004-08



\* Atomizing air/Pump pressure in bar  
\*\* Material pressure in bar

SATA Farbspritztechnik GmbH & Co. KG  
Domertalstraße 20  
70806 Kornwestheim  
Germany  
[www.sata.de](http://www.sata.de)